



Cadillac : SRX : 2016 : Front Wheel Drive  
 4-Wheel Total Alignment

Front : Left

Actual	Before	Specified Range
-0.6°	-0.6°	-1.4° 0.2°
4.1°	4.1°	3.7° 5.3°
0.17°	0.01°	0.00° 0.20°
12.0°	12.0°	
11.4°	11.4°	

Front : Right

Actual	Before	Specified Range
-1.2°	-1.2°	-1.4° 0.2°
4.4°	4.4°	3.7° 5.3°
0.16°	0.25°*	0.00° 0.20°
12.9°	12.8°	
11.6°	11.6°	

Camber  
 Caster  
 Toe  
 SAI  
 Included Angle  
 Turning Angle Diff.

Front

Cross Camber  
 Cross Caster  
 Cross SAI  
 Total Toe  
 Cross Turn Diff.

Actual	Before	Specified Range
0.7°	0.6°	-0.8° 0.8°
-0.2°	-0.2°	-0.8° 0.8°
-0.9°	-0.8°	
0.33°	0.25°	0.00° 0.40°

Rear : Left

Actual	Before	Specified Range
0.0°	-1.1°	-2.2° 0.2°
0.03°	-0.64°*	0.00° 0.20°

Rear : Right

Actual	Before	Specified Range
-0.7°	-1.6°	-2.2° 0.2°
0.07°	-0.56°*	0.00° 0.20°

Camber  
 Toe

Rear

Cross Camber  
 Total Toe  
 Thrust Angle

Actual	Before	Specified Range
0.7°	0.5°	
0.11°	-1.20°*	0.00° 0.40°
-0.02°	-0.04°	-0.30° 0.30°

\* This value is not within specification. Tire wear, handling and safety problems may result.